

Marke: SUNWARD
Modell: SWE 08B

Preis: POA

Ref: SUN5002

Marke/Modell: SUNWARD SWE 08B

Jahr: 2025

Bedingung: Brand New

Zusätzliche Daten.:

- Machine weight: 1010kg
- 3 year full engine warranty
- Yanmar EU stage V engine
- Complete with 3 buckets
- Manual quick hitch
- Zero tail swing
- 2 speed tracking
- Expandable tracks







maintenance

able engine hood allows the exposure of most engine area to ease mrs.

1 Starter motor

2 Auxiliary water tank

3 Oil suction filter element

4 Oil return filter

5 Battery

6 pressure gauge

7 Fuel filter

8 Engine oil cap

9 Fuel tank cap

alized greasing

External centralized pressing gauge

SWEDDE Technical Parameters		
Type of cab	category	0.022
Bucket capacity (m³)	mm	820
Bucket width	mm	820
Machine weight	kg	1050
Overall length	mm	2440
Overall height	mm	2250
Overall width	mm	750
Ground clearance	mm	135
Brand	Manufacturer	
Model	270V750-PSU	
Displacement	L	0.57
Output	1000rpm	2.2/2.400
Max working height	mm	855
Max loading height	mm	2305
Max digging depth	mm	1855
Max digging reach	mm	3180
Max working radius (reaches)	mm	735.5
Front swing radius	mm	1225
Max swing radius	mm	750
Max digging force (mm)	MPa	5.8
Max digging force (mm)	MPa	9.8
Track	Rubber crawler	
Type	mm	380
Track length	mm	3298
Length to corner of roller	mm	975
Undercarriage	mm	560/920
Length to center of track	mm	2.5/2.5
Traveling speed (high/low)	km/h	8.2
Traveling speed	km/h	24.5
Forward pressure	MPa	24.5
Grabbability	mm	100
Dozer size	mm	225/1000
Hydraulic pumps	mm	225/225
Displacement	L/min	3.6
Hydraulic pressure	MPa	27.5
Hydraulic oil tank capacity	L	9.5

Load Capability:

Lift Point	Lift Point Radius (MAX)	Lift Point Radius (2.0m)	Lift Point Radius (1.0m)			
Overloading	Overloading	Overloading	Overloading			
2.0m	119.60"	88.6	129.20"	107.10	416.40"	264.00
1.0m	157.80"	61.9	135.10	94.90	416.40"	264.00
0.0m	196.20"	70.1	124.90"	86.40	416.40"	264.00
-1.0m	205.80"	127.0			287.10"	243.40

Notes:

- Load with "is limited by hydraulic capacity and based on ISO 10547. Rated loads do not exceed 87% of hydraulic cap.
- Load without "is limited by lifting load and based on ISO 15847. Rated loads do not exceed 75% of lifting capacity.
- The excavator bucket, hook, and other lifting accessories are not included in this table.

Eingetragen in England und Wales Firmennummer: 03184184