

Marca: SUNWARD
Modelo: SWE 08B

Precio: £11,500

Ref: SUN5002

Marca / modelo: SUNWARD SWE 08B

Año: 2025

Condición: Brand New

Otras especific.:

- Machine weight: 1010kg
- 3 year full engine warranty
- Yanmar EU stage V engine
- Complete with 3 buckets
- Manual quick hitch
- Zero tail swing
- 2 speed tracking
- Expandable tracks







maintenance

able engine hood allows the exposure of most engine area to ease mrs.

1 Starter motor

2 Auxiliary water tank

3 Oil suction filter element

4 Oil return filter

5 Battery

6 pressure gauge

7 Fuel filter

8 Engine oil cap

9 Fuel tank cap

alized greasing

External centralized pressing gauge

SWEDDE Technical Parameters		
Type of cab	category	
Bucket capacity (m³)	0.822	
Bucket width	mm	820
Machine weight	kg	1850
Overall length	mm	2440
Overall height	mm	2250
Overall width	mm	750
Ground clearance	mm	135
Brand	Yanmar	
Model	27HV75D-PSU	
Displacement	L	0.57
Output	1000rpm	2.2/2400
Max working height	mm	3555
Max loading height	mm	2395
Max digging depth	mm	1855
Max digging reach	mm	3180
Max digging angle (vertical)	°	75.5
Front swing radius	mm	1221
Swing radius	mm	750
Max digging force (1 arm)	kN	5.8
Max digging force (2 arms)	kN	9.8
Track	Rubber crawler	
Track width	mm	380
Track length	mm	3198
Length to corner of roller	mm	975
Undercarriage		
Length to center of track	mm	560/520
Traveling speed (high/low)	km/h	2.5/2.5
Gradeability	°	30
Swing speed	°/min	8.2
Forward pressure	kg	24.5
Weight	mm	750/1050
Dozer size	mm	590
Hydraulic pumps	Type	3 Gear pump
Displacement	L/min	97.5
Hydraulic pressure	MPa	21.5
Flow rate (l/min)	L/min	50
Hydraulic oil tank capacity	L	9.5

Load Capability:

Lift Point	Lift Point Radius (MAX)	Lift Point Radius (2.0m)	Lift Point Radius (1.0m)			
Over-hauling	Over-hauling	Over-hauling	Over-hauling			
2.0m	119.60"	88.6	129.20"	107.10		
1.0m	157.80"	61.9	135.10	94.90	416.40"	264.00
0.5m	196.20"	70.1	124.90"	86.40	446.10"	262.20
0.1m	205.80"	127.0			287.10"	243.40

Notes:

- Load with "1" is limited by hydraulic capacity and based on ISO 10547. Rated loads do not exceed 87% of hydraulic cap.
- Load without "1" is limited by lifting load and based on ISO 15847. Rated loads do not exceed 75% of lifting capacity.
- The excavator bucket, hook, and other lifting accessories are not included in this table.

Registrada en Inglaterra y Gales Número de empresa: 03184184