

Make: SUNWARD
Model: SWE 08B

Price: £11,950

Ref: SUN5002

Make / Model: SUNWARD SWE 08B

Year: 2025

Condition: Brand New

Additional Spec:

- Machine weight: 1010kg
- 3 year full engine warranty
- Yanmar EU stage V engine
- Complete with 3 buckets
- Manual quick hitch
- Zero tail swing
- 2 speed tracking
- Expandable tracks







maintenance

able engine hood allows the exposure of most engine area to ease mrs.

1. Starter motor
2. Auxiliary water tank
3. Oil suction filter element
4. Oil return filter
5. Battery
6. pressure gauge
7. Fuel filter
8. Engine oil cap
9. Fuel tank cap

alized greasing

External centralized pressing gauge

SUNWARD Technical Parameters

Type of cab	category
Bucket capacity (m³)	0.822
Bucket width	mm 820
Machine weight	kg 1850
Overall length	mm 2440
Overall height	mm 2250
Overall width	mm 750
Ground clearance	mm 135
Brand	Sunward
Model	270V750-PSU
Displacement	L 0.57
Output	8800W
Max working height	mm 3.2/2.450
Max loading height	mm 2395
Max digging depth	mm 1855
Max digging reach	mm 3180
Max digging angle (vertical)	° 75/53
Front swing angle	mm 1221
Max swing radius	mm 750
Max digging force (m³)	5.8
Max digging force (m³)	9.4
Track	Rubber crawler
Track width	mm 380
Track length	mm 3198
Length to corner of roller	mm 975
Undercarriage	
Center to center of track	mm 560/520
Traveling speed (high/low)	km/h 2.5/1.5
Swing speed	deg 8.2
Forward pressure	kg 24.5
Dozer size	mm 590
Hydraulic pumps	1. 3.0L pump
Displacement	L 97.5
Hydraulic pressure	MPa 21.16
Flow rate (l/min)	50
Hydraulic oil tank capacity	L 9.5

Load Capability:

Lift Point	Lift Point Radius (MAX)	Lift Point Radius (2.0m)	Lift Point Radius (1.0m)			
Overloading	Overloading	Overloading	Overloading			
2.0m	119.60"	88.6	129.20"	107.10		
1.0m	157.80"	61.9	135.10	94.90	416.40"	264.00
0.5m	196.20"	70.1	124.90"	86.40	446.10"	262.20
0.1m	205.80"	127.0			287.10"	243.40

Notes:

- Load with "1" is limited by hydraulic capacity and based on ISO 10547. Rated loads do not exceed 87% of hydraulic cap.
- Load without "1" is limited by lifting load and based on ISO 15847. Rated loads do not exceed 75% of lifting capacity.
- The excavator bucket, hook, and other lifting accessories are not included in this table.

Incorporated in England and Wales Company number: 03184184