

Make: SUNWARD
Model: SWE 35UF

Price: POA

Ref: SUN5008

Make / Model: SUNWARD SWE 35UF

Year: 2025

Condition: Brand New

Additional Spec:

- Machine weight: 3850kg
- 5 year warranty
- 3 year full engine warranty
- Kubota EU stage V engine
- Complete with 3 buckets
- Hydraulic quick hitch
- Zero tail swing
- 2 speed tracking









WORKING RANGE

2700 SERIES

- Max. counterweight height: 4000 mm
- Max. loading height: 2,400 mm
- Max. lifting depth: 2,000 mm
- Max. reach to the ground: 1,500 mm
- Max. reach: 1,000 mm
- Max. reach (with 1.5m Jib): 1,500 mm
- Max. reach (with 3m Jib): 2,000 mm
- Max. reach (with 4.5m Jib): 2,500 mm
- Max. reach (with 6m Jib): 3,000 mm
- Max. reach (with 7.5m Jib): 3,500 mm
- Max. reach (with 9m Jib): 4,000 mm
- Max. reach (with 10.5m Jib): 4,500 mm
- Max. reach (with 12m Jib): 5,000 mm
- Max. reach (with 13.5m Jib): 5,500 mm
- Max. reach (with 15m Jib): 6,000 mm
- Max. reach (with 16.5m Jib): 6,500 mm
- Max. reach (with 18m Jib): 7,000 mm
- Max. reach (with 19.5m Jib): 7,500 mm
- Max. reach (with 21m Jib): 8,000 mm
- Max. reach (with 22.5m Jib): 8,500 mm
- Max. reach (with 24m Jib): 9,000 mm
- Max. reach (with 25.5m Jib): 9,500 mm
- Max. reach (with 27m Jib): 10,000 mm
- Max. reach (with 28.5m Jib): 10,500 mm
- Max. reach (with 30m Jib): 11,000 mm
- Max. reach (with 31.5m Jib): 11,500 mm
- Max. reach (with 33m Jib): 12,000 mm
- Max. reach (with 34.5m Jib): 12,500 mm
- Max. reach (with 36m Jib): 13,000 mm
- Max. reach (with 37.5m Jib): 13,500 mm
- Max. reach (with 39m Jib): 14,000 mm
- Max. reach (with 40.5m Jib): 14,500 mm
- Max. reach (with 42m Jib): 15,000 mm
- Max. reach (with 43.5m Jib): 15,500 mm
- Max. reach (with 45m Jib): 16,000 mm
- Max. reach (with 46.5m Jib): 16,500 mm
- Max. reach (with 48m Jib): 17,000 mm
- Max. reach (with 49.5m Jib): 17,500 mm
- Max. reach (with 51m Jib): 18,000 mm
- Max. reach (with 52.5m Jib): 18,500 mm
- Max. reach (with 54m Jib): 19,000 mm
- Max. reach (with 55.5m Jib): 19,500 mm
- Max. reach (with 57m Jib): 20,000 mm
- Max. reach (with 58.5m Jib): 20,500 mm
- Max. reach (with 60m Jib): 21,000 mm
- Max. reach (with 61.5m Jib): 21,500 mm
- Max. reach (with 63m Jib): 22,000 mm
- Max. reach (with 64.5m Jib): 22,500 mm
- Max. reach (with 66m Jib): 23,000 mm
- Max. reach (with 67.5m Jib): 23,500 mm
- Max. reach (with 69m Jib): 24,000 mm
- Max. reach (with 70.5m Jib): 24,500 mm
- Max. reach (with 72m Jib): 25,000 mm
- Max. reach (with 73.5m Jib): 25,500 mm
- Max. reach (with 75m Jib): 26,000 mm
- Max. reach (with 76.5m Jib): 26,500 mm
- Max. reach (with 78m Jib): 27,000 mm
- Max. reach (with 79.5m Jib): 27,500 mm
- Max. reach (with 81m Jib): 28,000 mm
- Max. reach (with 82.5m Jib): 28,500 mm
- Max. reach (with 84m Jib): 29,000 mm
- Max. reach (with 85.5m Jib): 29,500 mm
- Max. reach (with 87m Jib): 30,000 mm
- Max. reach (with 88.5m Jib): 30,500 mm
- Max. reach (with 90m Jib): 31,000 mm
- Max. reach (with 91.5m Jib): 31,500 mm
- Max. reach (with 93m Jib): 32,000 mm
- Max. reach (with 94.5m Jib): 32,500 mm
- Max. reach (with 96m Jib): 33,000 mm
- Max. reach (with 97.5m Jib): 33,500 mm
- Max. reach (with 99m Jib): 34,000 mm
- Max. reach (with 100.5m Jib): 34,500 mm
- Max. reach (with 102m Jib): 35,000 mm
- Max. reach (with 103.5m Jib): 35,500 mm
- Max. reach (with 105m Jib): 36,000 mm
- Max. reach (with 106.5m Jib): 36,500 mm
- Max. reach (with 108m Jib): 37,000 mm
- Max. reach (with 109.5m Jib): 37,500 mm
- Max. reach (with 111m Jib): 38,000 mm
- Max. reach (with 112.5m Jib): 38,500 mm
- Max. reach (with 114m Jib): 39,000 mm
- Max. reach (with 115.5m Jib): 39,500 mm
- Max. reach (with 117m Jib): 40,000 mm
- Max. reach (with 118.5m Jib): 40,500 mm
- Max. reach (with 120m Jib): 41,000 mm
- Max. reach (with 121.5m Jib): 41,500 mm
- Max. reach (with 123m Jib): 42,000 mm
- Max. reach (with 124.5m Jib): 42,500 mm
- Max. reach (with 126m Jib): 43,000 mm
- Max. reach (with 127.5m Jib): 43,500 mm
- Max. reach (with 129m Jib): 44,000 mm
- Max. reach (with 130.5m Jib): 44,500 mm
- Max. reach (with 132m Jib): 45,000 mm
- Max. reach (with 133.5m Jib): 45,500 mm
- Max. reach (with 135m Jib): 46,000 mm
- Max. reach (with 136.5m Jib): 46,500 mm
- Max. reach (with 138m Jib): 47,000 mm
- Max. reach (with 139.5m Jib): 47,500 mm
- Max. reach (with 141m Jib): 48,000 mm
- Max. reach (with 142.5m Jib): 48,500 mm
- Max. reach (with 144m Jib): 49,000 mm
- Max. reach (with 145.5m Jib): 49,500 mm
- Max. reach (with 147m Jib): 50,000 mm
- Max. reach (with 148.5m Jib): 50,500 mm
- Max. reach (with 150m Jib): 51,000 mm
- Max. reach (with 151.5m Jib): 51,500 mm
- Max. reach (with 153m Jib): 52,000 mm
- Max. reach (with 154.5m Jib): 52,500 mm
- Max. reach (with 156m Jib): 53,000 mm
- Max. reach (with 157.5m Jib): 53,500 mm
- Max. reach (with 159m Jib): 54,000 mm
- Max. reach (with 160.5m Jib): 54,500 mm
- Max. reach (with 162m Jib): 55,000 mm
- Max. reach (with 163.5m Jib): 55,500 mm
- Max. reach (with 165m Jib): 56,000 mm
- Max. reach (with 166.5m Jib): 56,500 mm
- Max. reach (with 168m Jib): 57,000 mm
- Max. reach (with 169.5m Jib): 57,500 mm
- Max. reach (with 171m Jib): 58,000 mm
- Max. reach (with 172.5m Jib): 58,500 mm
- Max. reach (with 174m Jib): 59,000 mm
- Max. reach (with 175.5m Jib): 59,500 mm
- Max. reach (with 177m Jib): 60,000 mm
- Max. reach (with 178.5m Jib): 60,500 mm
- Max. reach (with 180m Jib): 61,000 mm
- Max. reach (with 181.5m Jib): 61,500 mm
- Max. reach (with 183m Jib): 62,000 mm
- Max. reach (with 184.5m Jib): 62,500 mm
- Max. reach (with 186m Jib): 63,000 mm
- Max. reach (with 187.5m Jib): 63,500 mm
- Max. reach (with 189m Jib): 64,000 mm



Page: 4